



GN 155 Set

- Elegant floor stand
- Integrated LED ring
- For use with five different capsule modules
- Rugged all-metal construction

Elegant gooseneck module with heavy, shock mounted floor stand in matte gray finish for use with all Discreet Acoustics Capsule Modules. Integrated LED ring status indicator. Suited for stand-alone use on stage or in front of a lectern. Two integrated flexible gooseneck sections allow optimum alignment with talkers of different heights or positions. A supplied screw-on extension tube can be used to place the microphone higher for tall talkers. The supplied 10 m (33 ft.) cable with XLR phantom power adapter is long enough to reach the edge of most stages with no extension cable. For use as a lectern microphone in worship centers, halls etc.

Available capsule modules for GN 155 Set: CK 31, CK 32, CK 33, CK 47, CK 80.

Specifications

Bass filter	250 Hz, -10 dB at 50 Hz
Impedance	<=600 ohms
Recommended load impedance	>=2,000 ohms
Supply voltage	9 to 52 V phantom power to DIN/IEC
Current consumption	<3 mA
Connector	3-pin male XLR

Cable	10 m (33 ft.)
Finish	matte dark grey
Dimensions	180 x 1,490 mm (7.1 in. x 4 ft. 11 in.)
Net weight	3.6 kg (8 lbs.)
Shipping weight	4.8 kg (10.6 lbs.)

Engineer's specifications

The installation module shall consist of a 1490 mm long gooseneck module and a heavy-duty stand with shock isolation pad for connection to various capsule modules. Two integrated gooseneck sections shall provide for optimal microphone alignment with talkers of various heights or with specific sound source positions. The installation module shall be finished in multilayer dark gray enamel. A screw-on extension stub shall be included with the installation module. Net/shipping weight: 3.6/4.8 kg (8/10.6 lbs.).